







Model: C-L150M82				
		Specifications Name: Semi-hermetic Compressor Model: C-L150M82 Evaporating Temp.: $-40^{\circ} \div -5^{\circ}$ Ambient Temp.: $5^{\circ} \div 40^{\circ}$ Nominal Output: 15KW Power Source: 380V-415V/440V 3Phase 50Hz Refrigerant: R22		
Compressor Model		C-L150M82		
Nominal Output		15		
Power Source		380-415V 3 Phase 50Hz	440V 3 Phase 60Hz	
Specification	Evaporating Temp.	$-40^{\circ} \div -5^{\circ}$		
	Refrigerant	R22		
	Cooling Mode	Air Cooling/Liquid Injection		
Rated Specification	Capacity	W(Kcal/h)	30300(26050)	36500(31380)
	Input Power	W	13800	17300
	Current	A	26.2	27.7
Weight		KG	199.5	

Model: C-L105M81				
		Specifications Name: Semi-hermetic Compressor Model: C-L105M81 Evaporating Temp.: $-40^{\circ} \div -5^{\circ}$ Ambient Temp.: $5^{\circ} \div 40^{\circ}$ Nominal Output: 10.5KW Power Source: 380V-415V/440V 3Phase 50Hz Refrigerant: R22		
Compressor Model		C-L105M81		
Nominal Output		10.5		
Power Source		380-415V 3 Phase 50Hz	440V 3 Phase 60Hz	
Specification	Evaporating Temp.	$-40^{\circ} \div -5^{\circ}$		
	Refrigerant	R22		
	Cooling Mode	Air Cooling/Liquid Injection		
Rated Specification	Capacity	W(Kcal/h)	20930 (18000)	25000 (21500)
	Input Power	W	9750 $\pm 10\%$	11900 $\pm 10\%$
	Current	A	17.9 $\pm 10\%$	18.9 $\pm 10\%$
Weight		KG	154.5	

Model: C-L90M81				
		Specifications Name: Semi-hermetic Compressor Model: C-L90M81 Evaporating Temp.: $-40^{\circ} \div -5^{\circ}$ Ambient Temp.: $5^{\circ} \div 40^{\circ}$ Nominal Output: 7.5KW Power Source: 380V-415V/440V 3Phase 50Hz Refrigerant: R22		
Compressor Model		C-L90M81		
Nominal Output		7.5		
Power Source		380-415V 3 Phase 50Hz	440V 3 Phase 60Hz	
Specification	Evaporating Temp.	$-40^{\circ} \div -5^{\circ}$		
	Refrigerant	R22		
	Cooling Mode	Air Cooling/Liquid Injection		
Rated Specification	Capacity	W(Kcal/h)	17670 (15200)	21160 (18200)
	Input Power	W	7.97 $\pm 10\%$	9.87 $\pm 10\%$
	Current	A	14.9 $\pm 10\%$	15.4 $\pm 10\%$
Weight		KG	147.5	

Model: C-L55M8C				
		Specifications Name: Semi-hermetic Compressor Model: C-L55M8C Evaporating Temp.: $-40^{\circ} \div -5^{\circ}$ Ambient Temp.: $5^{\circ} \div 40^{\circ}$ Nominal Output: 5.5KW Power Source: 380V-415V/440V 3Phase 50Hz Refrigerant: R22		
Compressor Model		C-L55M8C		
Nominal Output		5.5		
Power Source		380-415V 3 Phase 50Hz	440V 3 Phase 60Hz	
Specification	Evaporating Temp.	$-40^{\circ} \div -5^{\circ}$		
	Refrigerant	R22		
	Cooling Mode	Air Cooling/Liquid Injection		
Rated Specification	Capacity	W(Kcal/h)	2919 (2510)	11281 (9700)
	Input Power	W	2920	5250
	Current	A	8.1	11.1
Weight		KG	100	

Model: C-L52M8C				
		Specifications Name: Semi-hermetic Compressor Model: C-L52M8C Evaporating Temp.: $-40^{\circ} \div -5^{\circ}$ Ambient Temp.: $5^{\circ} \div 40^{\circ}$ Nominal Output: 4.5KW Power Source: 380V-415V/440V 3Phase 50Hz Refrigerant: R22		
Compressor Model		C-L52M8C		
Nominal Output		4.5		
Power Source		380-415V 3 Phase 50Hz	440V 3 Phase 60Hz	
Specification	Evaporating Temp.	$-40^{\circ} \div -5^{\circ}$		
	Refrigerant	R22		
	Cooling Mode	Air Cooling/Liquid Injection		
Rated Specification	Capacity	W(Kcal/h)	2338 (2010)	10002 (8600)
	Input Power	W	2330	4650
	Current	A	7.3	9.8
Weight		KG	95	

Model: C-L37M8J				
		Specifications Name: Semi-hermetic Compressor Model: C-L37M8J Evaporating Temp.: $-40^{\circ} \div -5^{\circ}$ Ambient Temp.: $5^{\circ} \div 40^{\circ}$ Nominal Output: 3.7KW Power Source: 380V-415V/440V 3Phase 50Hz Refrigerant: R22		
Compressor Model		C-L37M8J		
Nominal Output		3.7		
Power Source		380-415V 3 Phase 50Hz	440V 3 Phase 60Hz	
Specification	Evaporating Temp.	$-40^{\circ} \div -5^{\circ}$		
	Refrigerant	R22		
	Cooling Mode	Air Cooling/Liquid Injection		
Rated Specification	Capacity	W(Kcal/h)	1523 (1310)	7548 (6490)
	Input Power	W	1740	3960
	Current	A	5.2	7.1
Weight		KG	92	